

APPROVAL SHEET

To :

Customer P/N :

UDE P/N : L22T007-2

Description : 2.5G Base –T

Single Port LAN Filter

Meet IEEE802.3 af standard



HF

Halogen
Free

Spec No.
LZ0457-00

Update Date
2021/3/11

Revision
C

Approved	Checked	Prepared



湧德電子 股份有限公司
UDE Corp.

桃園市(33852) 蘆竹區內溪路 68 巷13號

No.13, Ln. 68, Neixi Rd., Luzhu Dist., Taoyuan City (33852), Taiwan




TEL: 886-3-3242000 FAX: 886-3-3246611

<http://www.ude-corp.com/>

1. MECHANICAL DIMENSION


1.1 Product Dimension (Unit mm)

General Tolerance : X.X : ± 0.25
X.XX : ± 0.13



1.2 Recommended PCB Layout (Unit mm)

Component Side of Board

All dimension tolerances are $\pm 0.08\text{mm}$ unless otherwise specified

1.3 Order Information

<u>L</u>	<u>2</u>	<u>2</u>	<u>I</u>	<u>007</u>	-	<u>2</u>
A	B	C	D	E		F

A、Filter

B、SMD

C、24PIN

D、Operating Temperature : -40°C to +85°C

E、Product Numbering

F、PoE

2. SPECIFICATION

2.1 Designed for Ethernet 2.5G Base-T,Single port applications.

2.2 Supports 4 pairs of category 5 UTP cable.

2.3 Cable interface for isolation and low common mode emissions.

2.4 Design to meet IEEE 802.3af with 350mA balanced current.

2.5 Compliant with RoHS&Halogen Free requirements.

2.6 Operating and Storage Temperature

Operating Temperature : -40°C to +85°C

Storage Temperature : -40°C to +85°C


2.7 Packing Information

400 pcs finished goods per reel

3 reels(1200 pcs finished goods) per inner box

2 Inner boxes(2400 pcs finished goods) per master carton

3.1 Schematic



3.2 Electrical Specifications @25°C

Type : Balance low pass 100Ω impedance

3.2.1 Insertion loss :

1-50MHz	-0.5 dB Max
50-125MHz	-1.0 dB Max
125-200MHz	-2.0 dB Max

3.2.2 Return loss :

1~40MHz	-20 dB Min load 100Ω
40-200MHz	$-20 + 15 \cdot \log(\text{Freq MHz}/40\text{MHz})$ dB Min load 100Ω

3.2.3 Reflected CM to Diff Conversion(REF)

1MHz	-30 dB Min
50MHz	-30 dB Min
100MHz	-27 dB Min
200MHz	-24 dB Min

3.2.4 CM to DM Conversion(REF)

1-125MHz	-35 dB Min
----------	------------

3.2.5 Reflected Diff to CM Conversion(REF)

1-10MHz	-48 dB Min
10-200MHz	$-48 + 19 \cdot \log(\text{Freq MHz}/10\text{MHz})$ dB Min

3.2.6 CM to CM Attenuation (REF)

1-200MHz	-25 dB Min
----------	------------

3.2.7 Cross Talk (REF)

1-125 MHz	-30 dB Min
125-200 MHz	-25 dB Min

3.3 Inductance

@ 100KHz, 0.1V, 8mA DC BIAS 180uHMin

3.4 HiPot Test

@ 1500 Vrms

3.5 Turns Ratio


@ 1:1±5%

4. IR REFLOW TEMPERATURE PROFILE

Step#	Profile Feature	Condition/Duration
Step1	Ramp-up rate	3°C/sec max
Step2	Preheat : 150~200°C	Ta-Tb : 60-180sec
Step3	Ramp-up rate (TL to Tp)	3°C/sec max
	Temperature maintained above 217°C (TL)	tl : 60-150sec
Step4	Measured Peak temperature of pin (Tp) Set Reflow Peak Temp.	260°C
	The Time of Actual Peak temperature	20-40sec
Step5	Ramp-down rate	6°C/sec max
Note1	All temperatures refer to topside of the package, measured on the package body surface	
Note2	Time 25°C to peak temperature : 8 minutes max.	
Note3	It is not allowed to make a forced cooling in temperature falling range.	
Note4	The applicable condition refer to IPC/JEDEC J-STD-020D standard	

Table 1 Pb-Free Process-Classification Temperatures (Tp)

Package Thickness	Volume mm3 <350	Volume mm3 350-2000	Volume mm3 >2000
<1.6mm	260°C	260°C	260°C
1.6mm-2.5mm	260°C	260°C	260°C
>2.5mm	260°C	260°C	260°C



5. Revision History			
Issue Date	Revision	Comments	Operator
2019/2/20	A	Initial Release .	Wells
2020/5/9	B	Add logo label	AiAi
2021/3/11	C	Adjust Storage Temperature	AiAi