

APPROVAL SHEET

To :

Customer P/N :

UDE P/N : S71-ZZ-0001

Description : Double RJ45+USB 3.2 Gen1stack
Through Hole

10/100/1000 Base-T

Contact Area : Gold Flash

LED : L-Green; R-Yellow



Spec No.
S7120002-00

Update Date
2020/9/16

Revision
B

Approved	Checked	Prepared



湧德電子 股份有限公司
UDE Corp.

桃園市(33852) 蘆竹區內溪路 68 巷13號

No.13, Ln. 68, Neixi Rd., Luzhu Dist., Taoyuan City (33852), Taiwan



TEL: 886-3-3242000 FAX: 886-3-3246611

<http://www.ude-corp.com/>





1. MECHANICAL DIMENSION

Product Dimension

Unit:mm	General Tolerance :	X.X : ± 0.38
		X.XX : ± 0.20



Back View




DETAIL A


Recommended PCB Layout. Component side of board

All dimension units are "mm".

All dimension tolerances are $\pm 0.05\text{mm}$ unless otherwise specified.



Recommended Panel cutout




2. Packing Information

40 pcs finished goods per tray

4 trays(160 pcs finished goods) per inner box


4 Inner boxes(640 pcs finished goods) per master carton

3. Standard RJ45 Plug Specification



- All dimensions follow :
FCC subpart F, 68,500, Figure (C)(2)(i) & (C)(2)(ii) & (C)(3)(i)
IEC 60603-7
- All plugs must be meeting the requirements of plug Go & No-Go gauge.
Gauge follow : FCC subpart F, 68,500, Figure (C)(4)(i) & (C)(5)(i)
- There must be no damage to Housing and Locking Latch.
- There must be no nicks and cuts in cable.
- Durability : 750 cycles generally

4. USB 3.2 Standard-A Plug Specification



- All dimensions follow : Universal Serial Bus 3.0 Specification, Revision 1.0.

Figure 5-2. USB 3.1 Standard Plug-A interface dimensions

- Non-dimensions geometry for reference only, subject to change.
- Drawing for mating interface dimensions only.

5. REQUIREMENTS

Design and Construction

Product shall be of design, construction and physical dimensions specified on applicable.

Material

Terminal Parts (Underplating : 50 μ " min. Nickel overall)

RJ Terminal : Phosphor Bronze, Thickness=0.35mm

Finish : RJ Contact Area : Gold Flash

USB Terminal : Phosphor Bronze, Thickness=0.25mm

Finish : USB Contact Area : Gold Flash

Input&LED Terminal : Brass, Thickness=0.35mm

Finish : 100 μ " min. Matte Tin

USB Link Terminal : Brass, Thickness=0.35mm

Finish : 100 μ " min. Matte Tin

Plastic Parts

Housing : LCP, Black, <UL94V-0>

Case : LCP, Black, <UL94V-0>

Spacer : LCP, Black, <UL94V-0>

USB IM : PA6T, Black, <UL94V-0>

USB Input IM : PA6T, Black, <UL94V-0>

USB Input IM2 : LCP, Black, <UL94V-0>

RJ IM: LCP, Black, <UL94V-0>

Light Pipe: PC, Transparent, <UL94V-0>

Shield Parts

Front Shield : Stainless Steel, Thickness=0.20mm, unplating

Back Shield : Stainless Steel, Thickness=0.20mm, Pre-soldering

6. Operating and Storage Temperature

Operating Temperature : 0°C to +70°C

Storage Temperature : -40°C to +85°C

7. RJ45 specifications

Insulation Resistance : 500MΩ min.

Insertion force with the latch depressed : 20N max.

Removal force with the latch depressed : 20N max.

Locking Force of Plug Latch : 50N min. @ 60+/-5 sec.

Durability : 750 cycles

8. USB 3.2 Gen1 specifications

Insulation Resistance : 100MΩ min.

Dielectric Withstanding Voltage : 100VAC @1min

Insertion force : 35N max

Removal force : The connector extraction force shall not be less than 10N initial
and 8N after the specified insertion/extraction or durability cycles

Durability : 1500 cycles

9. Performance and Test Description


Product is designed to meet electrical, mechanical and environmental performance requirements specified in below table.

All tests are performed at ambient environmental conditions per MIL-STD-1344A and EIA-364 unless otherwise specified.

10 Packaging and Packing

All parts shall be packaged and packed to protect against physical damage, corrosion and deterioration during shipment and storage.




11. USB 3.2 GEN 1 Standard-A Schematic



USB 3.2 GEN 1 Standard-A connector Pin Assignment

Pin Number	Signal Name	Description	Mating Sequence
U1	VBUS	Power	Second
U2	D-	USB 2.0 Differential pair	Third
U3	D+		
U4	GND	Ground for power return	Second
U5	StdA_SSRX-	Super speed receiver differential pair	Last
U6	StdA_SSRX+		
U7	GND_DRAIN	Ground for Signal return	
U8	StdA_SSTX-	Surper speed transmitter differential pair	
U9	StdA_SSTX+		
Shell	Shield	Connector metal shell	First

12. ELECTRICAL CHARACTERISTICS @25°C



Emitting Color	λ_p (nm)	V_f @ $I_f=20mA$	I_r @ $V_r=5V$
Green	570	1.7 ~2.6 V	10 μ A max.
Yellow	588	1.7 ~2.6 V	10 μ A max.

Transmitter filter & Receiver filter

Type : Balance low pass 100Ω impedance

Insertion loss : 1 MHz -1.0dB Max.

100 MHz -1.4dB Max.

Return loss : 1~30MHz -16dB Min. load 100Ω

30~60MHz -14dB Min. load 100Ω

60~80MHz -10dB Min. load 100Ω

80~100MHz -8dB Min. load 100Ω

Common Mode Rejection

@1~100 MHz -30dB Min.

Cross Talk

@ 1~100MHz -30dB Min.

Inductance @ 100KHz, 0.1V

Input(TD1+, TD1-); (TD2+, TD2-); (TD3+, TD3-); (TD4+, TD4-) : 350 μH Typ.

HiPot Test

PHY Side(input) To Cable Side(output) : 1500Vac 60s or 2250Vdc 60s

13. WAVE SOLDERING TEMPERATURE PROFILE

Note :

The measuring point for the specified temperature shall be on the soldered part of the lead.

