

APPROVAL SHEET

To :

Customer P/N :

UDE P/N : SD20-ZZ-0001

Description : QSFP DD Cage 1X2
Press-fit
Without Lightpipe&heatsink
Packing With Tray



Spec No.	Update Date	Revision
SD2019001-00	2019/11/27	B

Approved	Checked	Prepared




湧德電子 股份有限公司
UDE Corp.

桃園市(33852) 蘆竹區內溪路 68 巷13號
No.13, Ln. 68, Neixi Rd., Luzhu Dist., Taoyuan City (33852), Taiwan
TEL: 886-3-3242000 FAX: 886-3-3246611
<http://www.ude-corp.com/>

1. MECHANICAL DIMENSION

1.1 CAGE assembly Dimension


General Tolerance : X.X : ± 0.38
X.XX : ± 0.20



1.2 Recommended PCB Layout

Component Side of Board

All dimension tolerances are $\pm 0.05\text{mm}$ unless otherwise specified



NOTES:


1. PADS AND VIAS CONNECT TO CHASSIS GROUND

RECOMMEND PADS TO BE 2.00mm SQUARE

2. RECOMMENDED THRU HOLE PLATING INCLUDES

HASL, OSP, OR IMMERSION (GOLD, SILVER, OR TIN)

3. 1.57mm MINIMUM PCB THICKNESS FOR SINGLE SIDED USE.



NOTES:

1. PADS AND VIAS CONNECT TO CHASSIS GROUND

RECOMMEND PADS TO BE 2.00mm SQUARE


2. RECOMMENDED THRU HOLE PLATING INCLUDES

HASL, OSP, OR IMMERSION (GOLD, SILVER, OR TIN)

3. 2.70mm MINIMUM PCB THICKNESS FOR BELLY TO BELLY SIDED USE.

RECOMMENDED MOTHER BOARD THROUGH HOLE DIMENSION



PLATED THROUGH HOLE	1.05 SHIELD PINS
FINISHED HOLE DIAMETER	1.05±0.05
DRILLED HOLE DIAMETER	1.15
COPPER PLATING	0.025





RECOMMENDED MOTHER BOARD THROUGH HOLE DIMENSION

1.3 Recommended Panel Cutout

PANELCUTOFF FOR SINGLE SIDE MOUNTING(SPRING FINGERS)



PANELCUTOFF FOR BELLY TO BELLY MOUNTING(SPRING FINGERS)



1.4 Packing Information

10 pcs finished goods per tray

8 trays(80 pcs finished goods) per master carton

2. REQUIREMENTS

2.1 Design and Construction

Product shall be of design, construction and physical dimensions specified on applicable.

2.2 Material

2.2.1 Shield Parts

2.2.1.1 Top Shell : Copper Alloy, Thickness=0.25mm

2.2.1.2 Bottom Shell : Copper Alloy, Thickness=0.25mm

2.2.1.3 EMI Spring Finger : Ph.Bronze, Thickness=0.08mm

Finish : 30μ" min. Nickel

2.2.1.4 Mid Ground : Copper Alloy, Thickness=0.25mm

2.3 Operating and Storage Temperature

Operating Temperature : -40°C to +85°C

Storage Temperature : -55°C to +105°C

2.4 QSFP CAGE specifications

Insertion force : 90 N max at a max. rate of 25.4mm per minute

(QSFP DD module to PCB connector and QSFP DD cage)

Extraction force : 50 N max at a max. rate of 25.4mm per minute

(QSFP DD module to PCB connector and QSFP DD cage)

Cage Retention (Latch strength) : 125N Min.

Durability : 100 cycles for standard class

2.5 Performance and Test Description

Product is designed to meet electrical, mechanical and environmental performance requirements specified in below table. All tests are performed at ambient environmental conditions per MIL-STD-1344A and EIA-364 unless otherwise specified.

2.6 Packaging and Packing

All parts shall be packaged and packed to protect against physical damage, corrosion and deterioration during shipment and storage.

3. Revision History

[illegible]